



T5 A7 STANDALONE FINGERPRINT

2007 VERSION STANDALONE FINGERPRINT T&A PRODUCTS COME INTO THE MARKET COMPLETELY!

Product Introduction

T5 and A7 were developed based on zem300 EDK with ZK optical sensor, Supporting Linux OS and USB 2.0 port. The attendance data and short messages can be randomly downloaded or uploaded with flash disk. The web server management software is embedded in A5 and A7, they are unnecessary to install Software. For daily maintenance and operation only need to input the IP address of the device after opening the IE browser, which is special suitable for 100-500 people attendance with decentralization or WAN administration.

Product Features

- 32 bit RISC embedded CPU
- Embedded LINUX operation system
- Standard TCP/IP communication Protocol
- U Disk that can support HOST, CLIENT.
- Embedded multi-language interface
- Can download the Time and Attendance Record through U disk.
- Broadcast both public and private short messages at fixed time.
- With WEB LINUX SERVER browser inside

Technical Specification

	T5
Register capacity	1500
Record capacity	50000
USB Flash Disk	
Operating system	Linux
Hardware platform	ZEM300
Algorithm version	2007Version ZK new algorithm
FAR	≤0.0001%
FRR	≤0.01%
Power	2A/5VDC
Communications	TCP/IP;RS485;RS232
Identification Time	≤2s
Keypad	16 Key Numeric Keypad with Back Lighting
LED Indicator	2 Array LED Indicators (Red, Green)
LCD	Character LCD 128 x 64
Operating Temperature	0°C~45°C
Operating Humidity	20%~80%
Language	English;chinese;other languages
Size	183 x 139 x 54mm
Standard Function	Work code, function key, scheduler bell
Optional	Simple access control(with C1 controller), backup power supply, Modem, Printer

	A7
Register capacity	1500
Transaction Storage	50000
USB Flash Disk	128M(Support USB 2.0 Protocol)
Operating system	Linux
Hardware platform	ZEM300
Algorithm version	2007Version ZK new algorithm
FAR	≤0.0001%
FRR	≤0.01%
Power	2A/5VDC
Communications	TCP/IP;RS485;RS232
Identification Time	≤2s
Keypad	16 Key Numeric Keypad with Back Lighting
LED Indicator	2 Array LED Indicators (Red, Green)
LCD	Character LCD 128 x 64
Operating Temperature	0°C~45°C
Operating Humidity	20%~80%
Language	English;chinese;other languages
Size	183 x 139 x 54mm
Standard Function	Work code, function key, scheduler bell, Web server
Optional	Simple access control(with C1 controller), backup power supply, Modem, Printer

ZKSoftware Inc.

Address: ZK Mansion, Wuhe Road, Gangtuo, Bantian, Buji Town, Longgang District, Shenzhen, China 518129

Tel: 86-755-83512040 Fax: 86-755-89602675 <http://www.zksoftware.com>

